

# Stobicoat® N

Coatings, Primers & Binders for  
Decorative & Industrial Surfaces

---

*The Stobicoat® N range includes aliphatic one and two-part stone binders and coatings for creating decorative, durable stone carpet or porous resin-bound surfaces, suitable for indoor and outdoor use. It supports outdoor sustainable urban drainage systems (SuDS) with a porous subbase. The binders work with kiln-dried aggregates like quartz, granite, marble, or recycled rubber, mixed with the correct binder-to-aggregate ratio using a forced mixer. Outdoor anti-slip properties can be enhanced by applying fine crushed glass as a finishing layer.*

## **Additional products are available to support installation, including:**

---

- Catalysts to shorten the cure times during cooler installation temperatures
- Stobielast® S solvent based and solvent free primers for subbase preparation before overlay of the decorative stone carpet
- Stobiblend Z trowelling aids for longer trowelling intervals before cleaning and to provide improved surface-smoothing action

The product range includes a hybrid, aromatic two-part stone binder, ideal for darker aggregates to minimize discoloration and as a cost-effective alternative to aliphatic binders.



## Stobicoat® N 2070

### Superior aliphatic UV-grade binder for optimum color stability

- Single component - no pre-mixing required with individual components
- Rigidity of cured resin provides extreme toughness to bound aggregates
- Better viscosity stability at colder temperatures
- Useable for all installation types
- Packaging starting at 5.8 kg (12.7 lbs)
- Solvent free

## Stobicoat® N 2075

### Aliphatic UV-grade binder for enhanced color stability

- Single component - no pre-mixing required with individual components
- Rigidity of cured resin provides extreme toughness to bound aggregates
- Useable for all installation types
- Packaging starting at 5.8 kg (12.7 lbs)
- Solvent free

## Stobicoat® N 2067

### Aliphatic UV-grade binder for enhanced color stability

- Two-component with easy to mix components
- Useable for all installation types
- Kit sizes starting at 6.5 kg (14.3 lbs)
- Solvent free

## Stobicoat® N 2072

### Economical aromatic non-UV grade binder

- Two-component with easy to mix components
- Recommended for use with darker aggregate blends where colour stability isn't critical
- Useable for all installation types
- Kit sizes starting at 7 kg (15.4 lbs)
- Solvent free

## Stobicoat® N 080

### Solvent-free primer for asphalt or concrete

## Stobicoat® N 100

### Solvent-based primer for asphalt or concrete

## Stobiblend Z 1966 / Z 1967

### Catalyst for accelerating cure below 15 °C (59 °F)

## Stobiblend Z 967

### Non-toxic & non-flammable trowelling aid

- Used on trowel equipment to provide smoother surface finish
- Low usage required with improved spread rate

**Disclaimer:** This bulletin is provided for general informational purposes only and should not be construed as advice on specific product usage. The manufacturer makes no warranty of merchantability or of fitness for a particular purpose. The buyer assumes all liability for incorrect or illegal use of this product. For additional information please review your local STOCKMEIER Urethanes' General Terms at <https://www.stockmeier.com/en/stockmeier-urethanes/general-terms/>, which apply for all commercial matters.